



Castrol EDGE Professional A3 5W-40

Boosted with TITANIUM FST™ - Strength for Maximum Performance

Description

Castrol EDGE Professional, boosted with **TITANIUM FST™**, provides outstanding oil strength for today's engines that work harder, with higher pressures than ever before.

Castrol EDGE is our strongest and most advanced range of engine oils.

Its **TITANIUM FST™** doubles its film strength, preventing oil film breakdown and reducing friction.

Castrol EDGE Professional with **TITANIUM FST™**: helping your engine perform at its best.

Castrol EDGE Professional is now certified CO2 neutral according to the highest global standards.

Engineered with Micro-Filtration in order to meet Castrol Professional's new quality standard and verified using Castrol's new Optical Particle Measurement System (OPMS) to guarantee product quality.

Application

Castrol EDGE Professional A3 5W-40 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A3/B4, A3/B3, API SN/CF or earlier specification 5W-40 lubricant.

Castrol EDGE Professional A3 5W-40 is approved by leading automobile manufacturers, please refer to the specifications section and your owners handbook.

Advantages

Castrol EDGE Professional A3 5W-40 gives you the confidence to demand maximum engine performance from today's latest technology, highly engineered engines that operate with tighter tolerances, requiring a high level of protection and low viscosity oils.

Castrol EDGE Professional A3 5W-40:

- Maximises short and long term engine performance
- Reduces engine deposits to help maximise engine response
- Delivers complete protection across a variety of engine speeds, conditions and temperatures
- Sustains maximum performance even when under pressure
- Independently proven to Improve engine efficiency
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperature
- Delivers and sustains maximum horsepower for longer, even when under pressure

Typical Characteristics

Name	Method	Units	Castrol EDGE Professional A3 5W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.8529
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.6
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5930
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	84
Viscosity Index	ASTM D2270	None	166
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	208
Ash, Sulphated	ASTM D874	% wt	1.15

Product Performance Claims

ACEA A3/B3, A3/B4
API SN/CF
BMW Longlife-01
MB-Approval 226.5/ 229.3/ 229.5
Porsche A40
Renault RN 0700 / RN 0710
VW 502 00/ 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional A3 5W-40
20 Jan 2015
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Ltd, Wakefield House, Pipers Way, Swindon, SN3 1RE, UK

www.castrol.com