



Castrol EDGE Professional V 0W-20

Boosted with TITANIUM FST™ - Strength for Maximum Performance

Description

Castrol EDGE Professional, boosted with **TITANIUM FST™**, provides outstanding oil strength for today's engines that work harder, with higher pressures than ever before.

Castrol EDGE is our strongest and most advanced range of engine oils. Its **TITANIUM FST™** doubles its film strength, preventing oil film breakdown and reducing friction.

Castrol EDGE Professional with **TITANIUM FST™**: helping your engine perform at its best.

Castrol EDGE Professional is now certified CO2 neutral according to the highest global standards. Engineered with Micro-Filtration in order to meet Castrol Professional's new quality standard and verified using Castrol's new Optical Particle Measurement System (OPMS) to guarantee product quality.

Application

Castrol EDGE Professional V 0W-20 is suitable for use in automotive gasoline engines where the manufacturer recommends an oil approved to Volvo VCC RBS0-2AE and SAE 0W-20 grade.

Volvo cars recommends Castrol EDGE Professional

Advantages

Castrol EDGE Professional V 0W-20 gives you the confidence to demand maximum engine performance from today's latest technology, highly engineered engines that operate with tighter tolerances, requiring lowest viscosity oils.

Castrol EDGE Professional V 0W-20:

- Maximises short and long term engine performance
- Reduces engine deposits to help maximise engine response
- Sustains maximum performance even when under pressure
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Delivers the highest levels of fuel efficiency
- Excellent performance at low temperatures

Typical Characteristics

Name	Method	Units	Castrol EDGE Professional V 0W-20
Density @ 15°C, Relative	ASTM D4052	g/ml	0.8421
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	8.8
Viscosity, CCS -35°C	ASTM D5293	mPa.s (cP)	4600
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	47
Viscosity Index	ASTM D2270	None	171
Ash, Sulphated	ASTM D874	% wt	0.83
Pour Point	ASTM D97	°C	-54
Flash Point, PMCC	ASTM D93	°C	206

Product Performance Claims

Volvo VCC RBS0-2AE

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional V 0W-20

09 Oct 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk