

Diesel System Cleaner

Product properties

Diesel System Cleaner removes operationally caused contamination sustained throughout the fuel system of diesel engines from the tank to the combustion chambers. It removes resin deposits, releases sticking injection nozzles and injection pumps, removes carbon residues and soot deposits within the entire upper cylinder area. It also lubricates and protects the diesel injection system and the entire upper cylinder area. Further the product prevents the oxidation of the fuel and the growth of microorganisms. The fuel atomization is improved.

Area of application

For use in diesel powered engines. Recommended for engines with particle filter, turbo and catalytic converter.

Application

Fill directly into the diesel tank before refueling or by using special cleaning equipment.

Consumption

300 ml treats up to 80 liters diesel. Mixing ratio: 1:250

Reaction time

while engine is running

Technical data

Physical state: liquid

Colour: brown

Odour: aromatic

Initial boiling point and boiling range: 200 - 210 °C

Flashpoint: 45 °C

Lower explosion limit: > 0,6 Vol.-%

Upper explosion limit: > 7,0 Vol.-%

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): > 8 hPa

Density at 68 °F: 0.83 - 0.86 g/cm³

Available sizes	Item no.	PU
300ml	33038	24
1L	51038	12



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advice. No liability for any printing errors. Technical modifications and errors are exempted.